

## i.Beat rock



### FEATURES

#### Playback functions

- Playable file formats: MP3, WMA, WAV
- Folder navigation
- M3U playlist support

#### Hardware

- Brilliant graphic LC display with backlighting
- Maximum operating period of approx. 10 hours (1 x AAA battery)
- Integrated voice recorder to record notes

#### Recording

- Record voice from integrated voice recorder (as WAV)

#### User interface

- German and English user guide
- ID3 tag display

### PACKAGE CONTENT

i.Beat rock, USB 2.0 cable, stereo headphones (integrated in the neck strap), AAA battery, quick guide

#### Additional functions

- 6 predefined equalizer
- Intro function
- Automatic shut-off with sleep timer function

#### Connections

- Earphone jack
- USB connection for fast data transfer

#### Communication with the PC

- Fast data transfer
- Suitable for Windows® 98(SE)<sup>1</sup>, ME, 2000, XP, Vista, Mac® OS X, Linux® from Kernel 2.4.x
- Mobile data storage device ("USB Stick Device")
- Firmware update possible

## TECHNICAL DATA

### HARDWARE

Memory	128 MB, 256 MB, 512 MB, 1 GB
Display	LCD (31 mm x 9.5 mm, 132 x 32 pixel, backlit)
Interface	USB 2.0, Earphone output (3.5 mm jack)
Dimensions (W x H x D)	75 mm x 37 mm x 15 mm
Weight	approx. 26 g (without battery)

### RECORD AND PLAYBACK

Playable file formats	MP3 (CBR/VBR, 32 - 320 kBit/s), WAV (8 kHz), WMA (48 - 192 kBit/s)
DRM (Digital Rights Management)	-
Playlists	M3U playlist
Equalizer	Bass, Jazz, Classical, Normal, Pop, Rock
File information	ID3 tag
Recording quality	Voice recorder, Voice recorder: WAV (8 kHz)

### FM RADIO

Radio / saved settings	-
Radio frequency range	-
Radio signal-to-noise ratio	-

### POWER

Power supply	1 x AAA battery
Maximum operating time	10 hours

### COMMUNICATION WITH THE PC

Supported operating systems	Microsoft Windows® 98(SE) <sup>1</sup> / ME / 2000 / XP / Vista, Mac® OS X from 10.3.x, Linux® from Kernel 2.4.x
Maximum data transfer rate (read / write)	1092 kB/s / 1092 kB/s
Software	-

### OTHER CHARACTERISTICS

File management	Folder navigation
Headphone output, impedance	5 mW (L) + 5 mW (R), Ohm
Frequency range	20 Hz - 20 kHz
Signal-to-noise ratio	> 90 dB
Languages	German, English

<sup>1</sup>: The driver can be obtained from our homepage at <http://www.trekstor.de>. We reserve the right to make changes and corrections.